



Hybrid Packing

ICP 924

Description:

Braided hybrid packing manufactured from combination of PTFE fiber yarn with aramid fiber yarn inside.

Key Features:

- It offers an excellent sealing and reliability in high performance duties.
- Hybrid packing that combines the properties of aramid and PTFE, resulting in a excellent product for high pressure valves and reciprocating duties.
- It is resistant to a wide range of media including water, oils, solvents and weak acids and alkalis.
- ICP 924 is self lubricating packing with superior gliding properties.



Applications:

- An exceptional packing for use with centrifugal and reciprocating pumps, mixers, agitator, etc.
- Suitable for a wide range of applications as food industry, petrochemical and pharmaceutical industry, paper & pulp industry, shipbuilding industry, waste water treatment plant, etc.

Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	50 / 725	25			
	200 / 2900	3	-200 / -328	280 / 536	2 - 12
	-	-			

Availability:

ICP 924 packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	25	40	55	65	100	160	195	230	260	315	410	520	580	640	775	1000
Roll Length	[m] / roll	60	37,5	27,2	23	25	15,6	12,8	10,8	9,6	15,9	12,2	9,6	8,6	7,8	6,5	5
Box weight	Kg	1,5			2,5			5									