



Vegetal Fiber Packing

ICP 906

Description:

Interbraided packing manufactured from high quality flax yarns added with PTFE dispersion and running-in lubricant.

Key Features:

- Well lubricated packing where maintains the shafts quality in hydraulic systems.
- An ideal packing for use with pumps where sludge, silt and sand resistance is required.
- Available for use with mildly corrosive chemicals such as oils, fats, water, weak solvents and fuel.



Applications:

- An exceptional packing for use in dynamic applications, such as centrifugal pumps and reciprocating type pumps.
- Suitable for a wide range of applications as ship-building industry, wastewater treatment plant, mining, agriculture, paper& pulp industry etc.

Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	15 / 218	8	-50 / -58	120 / 248	5 - 10
	30 / 435	2			
	-	-			

Availability:

ICP 906 packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	25	40	55	65	100	155	190	225	250	305	400	500	560	620	750	970
Roll Length	[m] / roll	60	37,5	27,2	23	25	16,1	13,2	11,1	10	16,4	12,5	10	8,9	8,1	6,6	5,2
Box weight	Kg	1,5				2,5				5							