



## PTFE Packing

# ICP 910M

## Description:

Braided packing manufactured from PTFE filaments added with PTFE dispersion and central core of temperature resistant elastomer.

## Key Features:

- Resistant to all media (pH 0 - 14), except for molten or dissolved alkali metals, elemental fluorine, hydrogen fluoride or materials that can generate these.
- Absorbs the eccentric action of worn shafts and bearings.
- Easy to install and to remove.
- High structural strength and cross-section.

## Applications:

- PTFE packing for valve applications requiring a pure, no-contaminating product with a high degree of resistance to chemical attack.
- ICP 910M is an exceptional packing which offers mechanical stability for products with abrasive content.



## Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	15 / 218	5	-200 / -328	260 / 500	0 - 14
	150 / 2176	2			
	250 / 3626	1			

## Availability:

ICP 910M packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	25	40	55	65	100	155	190	225	250	305	400	500	560	620	750	970
Roll Length	[m] / roll	60	37,5	27,2	23	25	16	13	11	10	16	12,5	10	8,9	8	6,6	5,2
Box weight	Kg	1,5			2,5						5						