



## PTFE Packing

# ICP 922

### Description:

Braided packing manufactured from PTFE filaments added with non-lubricated graphite.

### Key Features:

- Resistant to all media (pH 0 - 14), except for molten or dissolved alkali metals and elemental fluorine.
- It offers an excellent sealing and reliability in high performance duties.
- Easy to install and to remove.
- Thermally and chemically tolerant on a wide range of conditions.



### Applications:

- An exceptional packing for high pressure valves, with high degree of resistance to chemical attack.
- Suitable for a wide range of applications as petrochemical industry, power plants and refineries.

### Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	80 / 1160	10	-200 / -328	280 / 536	0 - 14
	200 / 2900	2			
	500 / 7251	1			

### Availability:

ICP 922 packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	20	30	40	50	75	115	140	165	185	225	300	370	450	460	560	720
Roll Length	[m] / roll	75	50	37,5	30	33,3	21,7	17,8	15,2	13,5	22,2	16,6	13,5	11,1	10,8	8,9	6,9
Box weight	Kg	1,5				2,5				5							