



Graphite Fiber Packing

ICP 925

Description:

Braided packing manufactured from high quality expanded graphite ribbons with a low chloride content, treated with special corrosion inhibitors.

Key Features:

- Low emission packing for be used with oxygen.
- ICP 925 is self-lubricating packing with superior gliding properties.
- Resistant to a wide range of chemicals with exception of powerful oxidizers.
- Excellent thermal conductivity and resilience, which is unaffected by changes in temperature and pressure.



Applications:

- High performance pump and valve packing for high temperature and pressure application.
- Suitable for a wide range of applications as petrochemical plants, chemical and process plants, power plants, refineries, boilers, etc.

Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	30 / 435	20	-200 / -328	650 / 1202	0 - 14
	250 / 3625	3			
	250 / 3625	-			

Availability:

ICP 925 packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	20	30	40	50	75	115	140	165	185	225	300	370	450	460	560	720
Roll Length	[m] / roll	75	50	37,5	30	33,3	21,7	17,8	15,2	13,5	22,2	16,6	13,5	11,1	10,9	8,9	6,9
Box weight	Kg	1,5			2,5			5									