



PTFE Packing

ICP 937

Description:

Braided packing manufactured from PTFE filaments added with high quality graphite based lubricant.

Key Features:

- It offers an excellent sealing and reliability in high performance duties.
- ICP 937 have been specially treated to incorporate a high quality graphite based lubricant.
- Excellent lubricity and high thermal conductivity.
- Easy to install and to remove.
- Thermally and chemically tolerant on a wide range of conditions.



Applications:

- An exceptional packing for centrifugal pumps, rotative, turbines, agitator valves, mixers, dryers and refiners.
- Suitable for a wide range of applications as metallurgical and chemical industry, paper & pulp, recycling plants, etc.

Technical Specifications:

	P (bar / psi)	V (m / s)	T (°C / °F)		pH
			Min	Max	
	50 / 725	25			
	200 / 2900	3	-200 / -328	260 / 500	0 - 14
	250 / 3625	-			

Availability:

ICP 937 packing is available in the following sizes and weights:

Section	mm	4	5	6	6,4	8	10	11	12	12,7	14	16	18	19	20	22	25
	in	-	3/16"	-	1/4"	5/16"	3/8"	7/16"	-	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	1"
grams per meter	[g] / [m]	25	40	55	65	100	160	195	230	260	315	410	520	580	640	775	1000
Roll Length	[m] / roll	60	37,5	27,3	23,1	25	15,6	12,8	10,8	9,6	15,8	12,2	9,6	8,6	7,8	6,5	5
Box weight	Kg	1,5			2,5				5								